

HOT WORK PRECAUTIONS CHECKLIST – HAZARDOUS AREAS

FILE NO.
WHS/149

NOTE: THIS AUTHORISATION FORM IS FOR HOT WORK PERFORMED IN OR ON HAZARDOUS AREAS. A HAZARDOUS AREA IS AN AREA IN WHICH FLAMMABLE LIQUIDS, VAPOURS OR GASES, COMBUSTIBLE LIQUIDS, DUSTS OR FIBRES, OR OTHER FLAMMABLE OR EXPLOSIVE SUBSTANCES MAY BE PRESENT. EG. Hydrogen plant, coal plant, chlorine plant, etc.

THIS HOT WORK AUTHORISATION IS ISSUED TO :

Name : _____

EMPLOYED BY :

Tarong Energy Contractor (detail) _____

TO CARRY OUT :

- Welding Cutting Heating Grinding
 Introduce Ignition source into hazardous area Operate a non certified crane / hoist in a hazardous area
 Other (detail) _____

LOCATED AT :

Workplace : _____ Specific Location : _____

ON : FROM : TO :

(Date): ____/____/____ (Time): _____ Hours. (Time): _____ Hours.

Note that the duration of this permit CAN NOT exceed 8 hours.

The Hot Work Officer, the Fire Watch and the Supervisor, must complete the Precautions Checklist on page 2 of this document, prior to issue of the Hot Work Authorisation

HOT WORK ISSUE	
AUTHORISATION ISSUED TO (HOT WORK OFFICER):	
Name:	
Signature:	
Date:	Time:
FIREWATCH RESPONSIBILITIES ACCEPTED BY (FIREWATCH):	
Name:	
Signature:	
Date:	Time:
AUTHORISATION ISSUED BY (SUPERVISOR):	
Name:	
Signature:	
Date:	Time:

HOT WORK COMPLETION	
HOT WORK COMPLETED BY (HOT WORK OFFICER):	
Name:	
Signature:	
Date:	Time:
FIREWATCH COMPLETED BY (FIREWATCH):	
Name:	
Signature:	
Date:	Time:
AUTHORISATION RETURNED TO (SUPERVISOR):	
Name:	
Signature:	
Date:	Time:

ON COMPLETION OF HOT WORK FORWARD THE ORIGINAL TO TARONG ENERGY O.H.& S. SECTION FOR REVIEW AND FILING.

HOT WORK PRECAUTIONS CHECKLIST – HAZARDOUS AREAS

FILE NO.
WHS/149

PRECAUTIONS	YES	NO
1. Can this work be relocated to an approved workshop or alternative method utilised? (Priority should be given to relocation of the work, to avoid Hot Work risks / introduction of ignition sources).		
2. Does this work require a “ Permit to Work ” under Tarong Energy Corporation’s formal Permit to Work system?		
3. Will this work be carried out in a Hazardous Area ? (An area in which an explosive atmosphere is present, or may be expected to be present, in quantities such as to require special precautions for the construction, installation and use of potential ignition sources. E.g. Presence of Flammable Liquids, Vapours or Gases, Combustible Liquids, Dusts or Fibres, or other Flammable or Explosive substances). EG. Hydrogen plant, coal plant, chlorine plant, etc.		If NO, use form T-1778
<ul style="list-style-type: none"> ➤ If YES :- A “Job Safety and Environment Analysis” must be completed for the Hot Work and/ or introduction of an ignition source into the hazardous area. ➤ Note - Standard JSEA 09/146081 is available for operation of cranes and hoists in a hazardous area. 		
<ul style="list-style-type: none"> ➤ If YES :- If Hazardous Area relates to Flammable Gases/Vapours than Air Quality Monitoring must be conducted and recorded on Page 4 of this checklist. 		
<ul style="list-style-type: none"> ➤ If YES :- Coal Dust Layering Inspection (Areas with dust zoning) If dust layering is covering the surfaces of the electrical equipment where the colour of the enclosure can not be seen then cleaning is required. Dust build up in the surrounding area should also be considered and should be cleaned if it can present a dust cloud hazard when disturbed. Note: Direct hosing of electrical equipment is to be avoided. 		
4. Have all flammable materials, liquids or gases been removed from within 15 metres of the Hot Work?		
5. Have all combustible materials been removed, covered, wetted down, or otherwise made safe within 15 metres of the Hot Work? Crane operation only requires a 2 metre exclusion zone as per the Hazardous Area Management procedure (ASM-PROC-MTC-MAN-06). (Fire watch is to monitor and re-wet / hose down at required intervals).		
6. Has a Fire watch been appointed? The Fire watch must be familiar with the duties of a fire watch and the specific functions required for the intended hot work. If NO , list the controls to be implemented to prevent a fire or explosion (ie. Wetting down area, etc). Note that ‘ NO ’ CANNOT be selected when grinding, welding, cutting, or any other hot work process that projects sparks or other flying hot debris. Note the Supervisor and H&S personnel must be consulted when selecting NO to ensure controls are satisfactory. - - -		

HOT WORK PRECAUTIONS CHECKLIST – HAZARDOUS AREAS

FILE NO.
WHS/149

7. Is automatic fire protection or fire detection installed in the area of the Hot Work?		
<p>➤ If YES :- Fire watch inspections, (to detect smouldering fires), are not required after the Hot Work is complete, if fire protection / detection systems are operational. If not operational see below for fire watch inspection requirements.</p>		
<p>➤ If NO :- Fire watch inspections, (to detect smouldering fires), must continue after Hot Work is complete. Frequency of inspections will be determined by the fire watch and supervisor in compliance with the checkbox statements below:</p> <p><input type="checkbox"/> Combustible material (including construction material) within 15m of hot work area = Hourly inspections for 4 hours</p> <p><input type="checkbox"/> No combustible material (including construction material) within 15m of hot work area = 1 inspection within an hour of work completion</p> <p>Fire watch inspections can cease if portable temporary fire detection system has been positioned at the hot work area and plant operators are informed of this.</p>		
8. Does this work require the isolation of fire protection or fire detection systems ?		
<p>➤ If YES :- A “Permit to Work” must be held by the O.I.C., and a “Fire Protection System Impairment Notice”, (Form T-1209), must be submitted to Insurers.</p>		
<p>➤ If YES :- A “Job Safety and Environment Analysis” must be completed for the Hot Work and/or introduction of an ignition source into the hazardous area.</p>		
9. Is suitable fire protection equipment provided for use at the area of Hot Work? List additional equipment if required: (e.g. Fire hose run out with line charged, additional extinguishers etc)		
-		
10. Have all drains, pits, and penetrations been checked and covered in the area of Hot Work?		
11. Have controls been implemented to contain sparks etc at the source (fire blanket, screens etc). Also consider the barricading requirements for areas below.		
12. Has adequate ventilation been provided in the vicinity of the Hot Work?		
13. Is Hot Work equipment in good repair?		
14. Is the hot work being performed in an operating plant area?		
<p>➤ If YES :- Notify the Operations representative for the area. Inform them of the scope of the intended hot work, location and expected duration. Discuss specific plant conditions and inform when hot work is complete.</p>		
15. Will this Hot Work be carried out by multiple Hot Work Officers ?		
<p>➤ If YES (for hot work) :- A “Hot Work Sign On/Off Sheet” (Form No. T-1054) must be attached and used to document compliance with this Hot Work Authorisation.</p> <p>➤ If YES (for Crane Operation):- A “Hot Work Sign On/Off Sheet” (Form No. T-1054) must be maintained and signed quarterly to document acknowledgement of suitable hazardous area management. <i>Crane operation in the coal plant area is the only exception regarding the maximum 8 hour work duration. Sign-on for this is quarterly as a JSEA is in place and the requirement still exist that all controls as per this authorisation forms are still implemented.</i></p>		



HOT WORK PRECAUTIONS CHECKLIST – HAZARDOUS AREAS

FILE NO.
WHS/149

THIS SECTION IS REQUIRED AND MANDATORY FOR WORK IN A HAZARDOUS AREA WITH FLAMMABLE GASES OR VAPOURS!

Pre Work Air Quality Check			O₂	LEL
			19.5 - 23.5%	< 5% of LEL
Date	Time		Test Results:	
Monitoring instrument was checked correct, using check gases, prior to testing this area.		The test results ARE / ARE NOT within the SAFE LIMITS listed above.		
Retesting of the atmosphere IS / IS NOT required? (circle) If retesting is required the test interval is..... or Continuous <input type="checkbox"/>				
Signed Gas Testing Officer:				

RETEST RECORD

Date	Time	O ₂ (19.5 – 23.5%)	LEL < 5% of LEL	Work is Safe to Continue	Gas Testing Officer Signature
				YES / NO	
				YES / NO	
				YES / NO	
				YES / NO	
				YES / NO	
				YES / NO	

Notes / Comments / Specific Requirements:

.....

.....

.....

.....

AUTHORISATION REVIEWED BY (O.H. & S. SECTION)

Name:

Signature:

Date: